

Luxerton Supreme 3mm

Luxerton Supreme is a non skid rug underlay for under rugs, produced out of a polyester fleece with a acrylic base adhesives, suitable for application on parquet, laminate, ceramic tiles, cork and LVT. This light weight rug underlay does not contain any softeners and creates a good and solid base for any rug and emphasize the luxury and comfort of the rug. Luxerton Supreme is suitable for domestic and commercial use.

- Light weight and easy to install
- Levels out small irregularities in the subfloor
- Produced environmental friendly
- Suitable in combination with floor heating

Installation method : Install Luxerton Supreme underneath the rug and make sure that Luxerton Supreme is resized 50mm smaller than the backing of the rug.

Direction of installation method NA

General building inspection license: NA

Thickness: 3 mm / $\pm 0,3$ mm - maximum tolerance 10%

Roll dimensions:
30m x 1m (30m²)
30m x 2m (60m²)

Special dimensions:

60cm x 130cm (19,50m ²)	(25 piece per box)
130cm x 190cm (19,76m ²)	(8 piece per box)
160cm x 230cm (18,40m ²)	(5 piece per box)
190cm x 290cm (22,04m ²)	(4 piece per box)

Weight: 250 gr/m² / ± 25 gr/m² - maximum tolerance 10%

Material: Top Layer : impregnated needle felt with a latex coating.

Packing: Roll: Printed LDPE bag
Pre-cut sizes: Transparent LDPE foil with insert.

Technical information:

Punctual conformity	: NA
Compressive strenght (test method: EN 826 + Annex a)	: NA
Caster chair test (Test method: EN 985)	: NA
Impact sound reduction (Test method: NA)	: NA
Thermal resistance (Test method: NA)	: 0,60 togs - 0,06m ² K/W
Fire retardency (Test methode: EN ISO 9239-1)	: NA
ASTM radial panel test (Test methode: ASTM E 648-06)	: NA
Russian requirements on fire safety (Test methode: FZ-123)	: NA

Installation instructions:

- Do not install Luxerton Supreme on a recently coating coated floor. To prevent any chemical reactions between Luxerton Supreme and the coating advice a waiting time of at east three months.
- make sure that the underfloor is absolutely dry and free of grit and dust.
- To cut the underpadding we recommend to use a scissors

Maintenance advice:

- Use only professional cleaning products which are suitable for your (hard) floor. Do not use the common household cleaning products. These can damage the protective film or lacquer of your floorcovering which can cause discolouration of the floorcovering. There is also the change the that future treatments will have problems bonding to the floorcovering.
- To prevent Luxerton Supreme from sticking to the subfloor we advise to ventilate the rug underlay from time to time. Use this open time to clean the subfloor with damp cloth.
- Luxerton Supreme is sensitive when exposed to sunlight for longer periods, resulting in dehydration.
- Luxerton Superior is not machine washable, only with hand wash at maximum 30°C.
- Do not tumble-dry Luxerton Supreme
- Do not iron Luxerton Supreme

Important:

In case the installation has not been done in accordance with the installation instructions, Estillon can not be held responsible for any damage or claim as a result of an incorrect installation. In case of doubt always consult your supplier.

