

# Luxerton Superior 3mm

Luxerton Superior is a non-skid rug underlay produced from high quality needle felt with a latex top layer and a non-skid latex bottom layer. This light weight rug underlay creates a comfortable, reliable, firm base for every carpet. Luxerton Superior does not contain any softeners and is suitable for application on parquet, laminate, ceramic tiles, marble, cork and LVT tiles. Luxerton Superior is suitable for domestic and project use.

- Light weight and easy to install
- Levels out small irregularities in the subfloor
- Extends the lifetime and conserves the original appearance of the rug
- Produced environmental friendly out of 100% recyclable materials
- Suitable in combination with floor heating

## Installation method :

Install Luxerton Superior underneath the rug with the printed side up. Make sure that Luxerton Superior is resized 50mm smaller than the backing of the rug.

NA

## Direction of installation method : General building inspection license:

NA

## Thickness:

3 mm /  $\pm 0,3$  mm - maximum tolerance 10%

## Roll dimensions:

20 m x 0,9 m =  $\pm 18$  m<sup>2</sup>  
20 m x 1,5 m =  $\pm 30$  m<sup>2</sup>  
20 m x 1,8 m =  $\pm 36$  m<sup>2</sup>  
20 m x 2,0 m =  $\pm 40$  m<sup>2</sup>

## Special dimensions:

75cm x 155cm (11,63 m<sup>2</sup>) / 10 pieces per box  
135cm x 195cm (26,33 m<sup>2</sup>) / 10 pieces per box  
165cm x 235cm (38,78 m<sup>2</sup>) / 10 pieces per box  
195cm x 295cm (57,52 m<sup>2</sup>) / 10 pieces per box

## Weight:

500 gram/m<sup>2</sup> /  $\pm 50$  gr/m<sup>2</sup> - maximum tolerance 10%

## Material:

Top Layer : Latex film with logo and pattern  
Middle layer: Polyester needle felt  
Bottom layer: Non-skid latex film

## Packing:

Roll: Printed LDPE bag  
Pre-cut sizes: Transparent LDPE foil with insert.

## Technical information:

<b>Punctual conformity</b>	: NA
<b>Compressive strenght</b> (test method: EN 826 + Annex a)	: NA
<b>Caster chair test</b> (Test method: EN 985)	: NA
<b>Impact sound reduction</b> (Test method: NA)	: NA
<b>Thermal resistance</b> (Test method: NA)	: 0,60 togs - 0,06m <sup>2</sup> K/W
<b>Fire retardency</b> (Test methode: EN ISO 9239-1)	: Cfl-S1* (*Tested in combination with an 80/20 Axminster carpet)
<b>ASTM radial panel test</b> (Test methode: ASTM E 648-06)	: NA
<b>Russian requirements on fire safety</b> (Test methode: FZ-123)	: NA

## Installation instructions:

- Make sure that the subfloor is completely dry and free of grease, stone-dust and dust.
- We advise the use of a sharp kitchen or carpet shear for resizing the rug underlay.
- Do not install Luxerton Superior on a recently coated floor. To prevent any chemical reactions between Luxerton Superior and the coating we advise a waiting time of at least three months.

## Maintenance advice:

- Use only professional cleaning products which are suitable for your (hard) floor. Do not use the common household cleaning products. These can damage the protective film or lacquer of your floorcovering which can cause discolouration of the floorcovering. There is also the change the that future treatments will have problems bonding to the floorcovering.
- To prevent Luxerton Superior from sticking to the subfloor we advise to ventilate the rug underlay from time to time. Use this open time to clean the subfloor with damp cloth.
- Luxerton Superior is sensitive when exposed to sunlight for longer periods, resulting in dehydration.
- Luxerton Superior is not machine washable, only with hand wash at maximum 30°C.
- Do not tumble-dry Luxerton Superior
- Do not iron Luxerton Superior

## Important:

*In case the installation has not been done in accordance with the installation instructions, Estillon can not be held responsible for any damage or claim as a result of an incorrect installation. In case of doubt always consult your supplier.*

