

# Luxerton Solid 5mm

Luxerton Solid is a non-skid rug underlay produced from high quality needle felt with a latex top layer and a non-skid bottom layer with a structure of studs. This light weight rug underlay creates a comfortable, reliable, firm base for every carpet. Luxerton Solid does not contain any softeners and is suitable for application on carpet. Luxerton Solid is suitable for domestic use.

- Light weight and easy to install
- Levels out small irregularities in the subfloor
- Extends the lifetime and conserves the original appearance of the rug
- Produced environmental friendly out of 100% recyclable materials
- Suitable in combination with floor heating

---

## Installation method :

Install Luxerton Solid underneath the rug with the printed side up. Make sure that Luxerton Solid is resized 50mm smaller than the backing of the rug.

NA

## Direction of installation method : General building inspection license:

NA

## Thickness:

5 mm /  $\pm 0,5$  mm - maximum tolerance 10%

## Roll dimensions:

25 m x 1 m =  $\pm 25$  m<sup>2</sup>  
25 m x 2 m =  $\pm 50$  m<sup>2</sup>

## Weight:

650 gram/m<sup>2</sup> /  $\pm 65$  gr/m<sup>2</sup> - maximum tolerance 10%

## Material:

Polyester Fleece

## Packing:

LDPE bag with inlay

## Technical information:

<i>Punctual conformity</i>	: NA
<i>Compressive strenght</i> (test method: EN 826 + Annex a)	: NA
<i>Caster chair test</i> (Test method: EN 985)	: NA
<i>Impact sound reduction</i> (Test method: NA)	: NA
<i>Thermal resistance</i> (Test method: NA)	: 0,60 togs - 0,06m <sup>2</sup> K/W
<i>Fire retardency</i> (Test methode: EN ISO 9239-1)	: NA
<i>ASTM radial panel test</i> (Test methode: ASTM E 648-06)	: NA
<i>Russian requirements on fire safety</i> (Test methode: FZ-123)	: NA

## Installation instructions:

- Make sure that the subfloor is completely dry and free of grease, stone-dust and dust.
- We advise the use of a sharp kitchen or carpet shear for resizing the rug underlay.

## Maintenance advice:

- To prevent Luxerton Solid from sticking to the subfloor we advise to ventilate the rug underlay from time to time. Use this open time to clean the subfloor with damp cloth.
- Luxerton Solid is sensitive when exposed to sunlight for longer periods, resulting in dehydration.
- Luxerton Solid is not machine washable.
- Do not tumble-dry Luxerton Solid
- Do not iron Luxerton Solid

## Important:

*In case the installation has not been done in accordance with the installation instructions, Estillon can not be held responsible for any damage or claim as a result of an incorrect installation. In case of doubt always consult your supplier.*

