



**estillon**  
FUNDAMENTAL FOR FLOORS SINCE 1965

# LUXERTON

## ANTI-SLIP UNDERLAYS

A nice rug or carpet makes your home snug and cosy. But then it does have to stay in place and you mustn't slip on it. After all, an ounce of prevention is worth a pound of cure. An anti-slip underlay helps with this.

With its Luxerton series of anti-slip underlays, Estillon has the solution in-house.



Luxerton Superior  
3 mm

Luxerton Supreme  
2.5 mm

Luxerton Standard  
2 mm

Luxerton Solid  
5 mm

- Lightweight and easy to install
- Levels small unevenness in the base floor
- Extends the lifespan and conserves the carpet's original appearance
- Produced in an environmentally friendly way and 100% recyclable Suitable in combination with radiant floor heating



**estillon**  
FUNDAMENTAL FOR FLOORS SINCE 1965

# LUXERTON

## ANTI-SLIP UNDERLAYS

### Specifications Luxerton range

	Luxerton Superior 3 mm	Luxerton Supreme 3 mm	Luxerton Standard 2 mm	Luxerton Solid 5 mm
<b>Thickness</b>	3 mm	3 mm	2 mm	5 mm
<b>Dimensions</b>	20m x 0,9m (18m <sup>2</sup> ) 20m x 1,5m (30m <sup>2</sup> ) 20m x 1,8m (36m <sup>2</sup> ) 20m x 2m (40m <sup>2</sup> ) 75cm x 155cm (11,63m <sup>2</sup> ) 10x 135cm x 195cm (26,33m <sup>2</sup> ) 10x 165cm x 235cm (38,78m <sup>2</sup> ) 10x 195cm x 295cm (57,52m <sup>2</sup> ) 10x	30m x 1m (30m <sup>2</sup> ) 30m x 2m (60m <sup>2</sup> ) 60cm x 130cm (19,50m <sup>2</sup> ) 25x 130cm x 190cm (19,76m <sup>2</sup> ) 8x 160cm x 230cm (18,40m <sup>2</sup> ) 5x 190cm x 290cm (22,04m <sup>2</sup> ) 4x	40m x 1m (40m <sup>2</sup> ) 40m x 2m (80m <sup>2</sup> ) 60cm x 130cm (27,30m <sup>2</sup> ) 35x 130cm x 190cm (34,58m <sup>2</sup> ) 14x 160cm x 230cm (36,80m <sup>2</sup> ) 10x 190cm x 290cm (38,57m <sup>2</sup> ) 7x 240cm x 340cm (40,80m <sup>2</sup> ) 5x	25m x 1m (25m <sup>2</sup> ) 25m x 2m (50m <sup>2</sup> )
<b>Weight</b>	500 gr/m <sup>2</sup>	250 gr/m <sup>2</sup>	150 gr/m <sup>2</sup>	650 gr/m <sup>2</sup>
<b>Material</b>	High quality needle felt with a latex top layer and a non-skid latex bottom layer	Polyester fleece with a acrylic base adhesives	Latex impregnated needle felt	Polyester Fleece
<b>Punctual conformity</b>	NA	NA	NA	NA
<b>High compression strength</b>	NA	NA	NA	NA
<b>Weelchair test</b>	NA	NA	NA	NA
<b>Impact sound reduction</b>	NA	NA	NA	NA
<b>Thermal resistance</b>	0.60 togs - 0.06m <sup>2</sup> K/W	0.60 togs - 0.06m <sup>2</sup> K/W	0.60 togs - 0.06m <sup>2</sup> K/W	0.60 togs - 0.06m <sup>2</sup> K/W
<b>Fire retardancy</b>	Cfl-S1	NA	NA	NA

MORE INFORMATION AT [WWW.ESTILLON.COM](http://WWW.ESTILLON.COM)



**estillon**  
GREEN CHOICE