

estillon
WE WILL IMPROVE YOUR FLOOR

LVT Multi-Fit 1.5mm

The universal subfloor offers exceptional stability and comfort for all living and working areas.

The universal subfloor for laminate, parquet, LVT click and LVT Dry Back. Suitable for private and commercial applications such as hotels, offices and shipbuilding.

The universal subfloor offers exceptional stability and comfort for all living and working areas.

Installation methods:

- Floating installation
Laminate, parquet and LVT-click
- Stick-down installation (single/double)
LVT-Dry Back

EN1365 Compliant

- Meets the increased requirements of :
MBAM/EPLF
- Sound reducing 18 dB ΔLw
- Pressure resistance > 500 kPa/m²
- Suitable for underfloor heating

Certification

- IMO / flame retardancy
- Indoor Air Quality A+
- LEED
- Bfl-S1 / fire retardancy
- TÜV Rheinland / impact sound reduction

LVT-Click/Parquet/Laminate

FLOORING

LVT MULTI FIT 1.5mm

MOISTURE BARRIER

UNDERFLOOR HEATING

SAND CEMENT FLOOR

LVT Dry Back



FLOORING

ADHESIVE

LVT MULTI FIT 1.5mm

ADHESIVE

SAND CEMENT FLOOR





estillon
WE WILL IMPROVE YOUR FLOOR

LVT Multi-Fit 1.5mm

The universal subfloor offers exceptional stability and comfort for all living and working areas.

Technical specs Multi-Fit

Technical Specifications

Radiated reduction walking sound RWS	Impact sound reduction IS	Levelling out point irregularities PC	Pressure resistance CS	Thermal resistance R	Shock load RLB	Heat resistance	Vapour resistance SD
30 %	18 dB	0,55 mm	503 kPa/m ²	0,012 m ² K/W	120 cm	Yes	< 75 m

Specifications

Article number	Supplied as	Length m	Width m	Thickness mm	Area m ²	Roll/Pal. St.	Pal m ²
114100111	Rolls	7,30	1,37	1,5	10,00	40	400

Estillon BV

Linie 25
NL-5405 AR Uden
info@estillon.nl

Estillon S.A.R.L

64 Rue Claude Chappe
FR-78370 Plaisir
info@estillon.fr

Estillon GmbH

Fössestraße 77c
DE-30451 Hannover
info@estillon.de

Estillon is part of  interfloor Group Limited

MORE INFORMATION AT WWW.ESTILLON.COM